



XT Series



The Extended Time Series (XT) of cryogenic refrigerators are designed for long-term storage of a variety of materials at cryogenic temperatures. This series also offers a low profile model (XTL), with 5" canisters.

Models	XTL3	XTL8	XT10	XT20	XT34	XT21-AI
Static Holding Time days (1)	27	80	100	230	340	221
Working Time days (2)	17	50	62	140	212	138
Evaporation Rate (1) liters/days	0.11	0.10	0.10	0.09	0.10	0.095
Liquid Nitrogen Capacity - liters	3	8	10	20.7	34	21
Weight Empty	- lbs. 7.2 - kg. 3.3	19.6 8.9	16.5 7.5	26 11.8	34.75 15.8	26 11.8
Weight Full (3)	- lbs. 12.5 - kg. 5.7	33.8 15.4	34.3 15.6	62.8 28.6	95.3 43.3	63.4 28.8
Neck Diameter	- in. 2.0 - mm. 51	2.0 51	2.0 51	2.0 51	2.0 51	2.18 55.4
Overall Height	- in. 17.2 - mm. 437	19 483	23.8 597	25.8 655	26.3 668	25.8 655
Overall Diameter	- in. 7.6 - mm. 193	15.6 396	11.4 290	15.6 396	18.8 478	15.6 396
Number of Canisters	6	6	6	6	6	6
Canister Dimensions (4)	- in. 1.5x5 - mm. 38x127	1.5x5 38x127	1.5x11 38x279	1.5x11 38x279	1.5x11 38x279	1.65 x 11 41.5 x 279
Number of 1.2 ml & 2.0 ml vials (5/cane)	NA	NA	150	150	150	210
Number of 1.2 ml & 2.0 ml vials (6/cane)	NA	NA	180	180	180	
Number of 1/2 cc straws (10/cane)	NA	NA	540	540	540	720
Number of 1.2 cc straws - Bulk (1 level)	750	750	NA	NA	NA	1122
Number of 1/2 cc straws - Bulk (2 levels)	NA	NA	1500	1500	1500	
Roller Base	N/A	R018-8C00	N/A	R018-8C00	R033-8C00	R018-8C00
Low-Level Alarm	N/A	N/A	N/A	R033-8C15	R033-8C15	R021-8C15

Features

- New Rugged Construction – ribbed high strength aluminum body, magniformed necktube design, and more durable paint
- Versatile storage system - convenient canister numbered index location ring and internal spider
- Superior vacuum performance with super insulation provides maximum holding times
- Security - Accessory low-level alarm is available with remote monitor capability
- Mobility - Roller bases are available for some models
- Lockable lids



(1) Evaporation rate and static holding time are nominal. Actual rate may be affected by the nature of the contents, atmospheric conditions, container history, and manufacturing tolerances.
 (2) Work time is an arbitrary, reference-only value to estimate container performance under the actual operating conditions.
 (3) Without canisters.
 (4) Canisters also available in 5.0 in. (127 mm) height for 10 XT, 20XT and 34XT.